



Technical Guidance

Technical Guidance Note
H1/05/05 on:

Safety Harnesses in Mobile Elevating Work Platforms

Boom Type Platforms

It is strongly recommended that a full body harness with an adjustable lanyard (used to provide work restraint and adjusted to be as short as possible) is used when working from a boom type Mobile Elevating Work Platform (MEWP).

This would include:

Static Booms (1b) and Mobile Booms (3b).



Vertical Lifts

It is not normally necessary for personnel working from a vertical lift to wear fall protection equipment, other than in exceptional circumstances.

This would include:

Static Verticals (1a), Mobile Verticals (3a) and Mast Climbing Work Platforms (MC).

The need for a fall protection system will be the outcome of a job specific risk assessment undertaken prior to work commencing and taking into consideration the manufacturer's operators' manual.

More details see overleaf or

www.ipaf.org



For information on preventing falls and on the use of harnesses and lanyards in MEWPs see:

HSE Information Leaflet MISC614 Preventing falls from boom-type mobile elevating platforms.

Available from the HSE website at
<http://www.hse.gov.uk/pubns/fallindx.htm>

This guidance note was issued by the Powered Access Interest Group, a joint committee of the International Powered Access Federation and the Construction Plant-Hire Association, with representatives from hire companies and the Health & Safety Executive, on 18.04.05.
(Ref IPAF TGN H1-2005)

www.ipaf.org

For information about IPAF's full range of training programmes for all kinds of MEWPs visit www.ipaf.org

Head Office:

IPAF, Bridge End Business Park, Milnthorpe LA7 7RH, UK.
Tel: +44 (0)15395 62444 Fax: +44 (0)15395 64686
info@ipaf.org www.ipaf.org

Switzerland:

IPAF-Basel, Aeschenvorstadt 71, CH-4051 Basel, Switzerland.
Tel: +41 (0)61 225 4407 Fax: +41 (0)61 225 4406
basel@ipaf.org



The world authority in powered access